



SMART S

2.370

 **Allowed user weight**
150 kg

 **Suitable for passenger transport**
Tested according to ISO 7176-19 (max. user weight 136 kg)





Optimised folding system
with compact folding
dimensions



Extremely low actuating forces



Individually adjustable
chassis



Unique side panel with
height adjustable armrest,
one handed operation

New Active Line

EFFICIENCY

- High part compatibility
- Little wear and proneness to repair through integral design of the frame and the quality of the attachment components
- Quick and long term assurance of spare parts provision through an area wide dealer structure

THERAPEUTIC BENEFIT

- Stabilization and mobilization of users with neurological diseases, through good support while sitting and low weight a.s.o.
- The straight front frame and swivel-away, removable leg supports make it easy to get close to everyday objects
- Folding mechanism for independent loading into a car
- Adaptable to functional changes of the user, e.g. by retrofitting electric drives
- Extensive equipment assortment for long-term users

FIELD OF USE

- For permanent and long term provision
- Very good suitability for many disease patterns, even for severely encumbered
- For users with remaining walking and standing abilities (standing transfer)
- With neurological diseases

ORDER

COST ESTIMATE

CUSTOM DESIGN

Please fax the completed order form to: 05733 922 9311

Customer service 05733 922 311

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Allowed user weight

150 kg



Suitable for passenger transport

Tested according to ISO 7176-19 (max. user weight 136 kg)



Hints

Our Terms and Conditions as stated at www.meyra.de/AGB shall apply
You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2024 – 31.12.2024.
Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check



Technical specifications

¹⁾ When using auxiliary drives, the permissible total weight must not be exceeded

Seat widths in mm	320/340/360/380/400/420/440/460/480/500/520
Width ready to drive in mm from	Seat width + 180
Width folded in mm from	280 with 0° wheel camber or 330 with 3° wheel camber
Seat depth in mm	380/400/420/440/460/480/500
Seat height front/rear in mm	400 to 540/370 to 530
Overall height in mm	Rear seat height + back support height
Back support height in mm	variable from 250 to 500 +25 mm
Arm support height in mm	ca. 170 - 245
Length with footrest in mm	880 - 1030 (depending on frame length, wheel size and axis position)
User weight	150 kg
Empty weight from	from 10.5 kg
Permissible overall weight	170 kg ¹⁾
Transport weight	6,5 kg
Rear wheel	560mm (22") / 600 mm (24") / 635 mm (25") / 660 mm (26")
Brake test according to STANDARD	7°

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

01 Frame shape / seat width / seat depth

	Frame short 79° (C-351)			Frame medium 79° (C-352)		Frame long 79° (C-353)	
	(C-368)	(C-615)	(C-784)	(C-618)	(C-619)	(C-787)	(C-792)
Seat width/Seat depth	SD 380 mm	SD 400 mm	SD 420 mm	SD 440 mm	SD 460 mm	SD 480 mm	SD 500 mm
SW 320 mm (C-32)							
SW 340 mm (C-34)							
SW 360 mm (C-36)							
SW 380 mm (C-38)							
SW 400 mm (C-40)							
SW 420 mm (C-342)							
SW 440 mm (C-344)							
SW 460 mm (C-46)							
SW 480 mm (C-48)							
SW 500 mm (C-350)							
SW 520 mm (C-952)							

including utensil pocket under the seat belt

Variable block

CODE	DESCRIPTION	TOTAL WIDTH
992	Varioblock for additional drives	+ 20 mm
	⚠ only necessary with selection of side panel CODE 81 or 84 in combination with Alber drives	

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

03 Front seat height (FSH) in combination with castor wheel (without seat cushion)

The maximum permissible seat height difference between the front and rear seat height is 90 mm

Front seat height in mm (FSH)

Code	Castor	400	410	420	430	440	450	460	470	480	490	500	510	520	530	540
151/908	Ø 100 Solid rubber black															
151/909	Ø 100 Solid rubber grey															
325/908	Ø 125 Solid rubber black															
325/909	Ø 125 Solid rubber grey															
327/908	Ø 142 Soft solid rubber black															
327/909	Ø 142 Soft solid rubber grey															
645	Ø 180 Pneumatic tires															
161	Ø 180 Solid rubber															

Front seat height (FSH) in combination with castor wheel (without seat cushion)

Front seat height in mm (FSH)

Code	Castor	400	410	420	430	440	450	460	470	480	490	500	510
2480	Ø 100 x 23 Lightwheel black												
2481	Ø 100 x 32 Castor aluminum silver												
2482	Ø 125 x 32 Castor aluminum silver												

 Tyres: CODE 2480 solid rubber, transparent/colored - CODE 2481/2482 solid rubber black

Seat height front in combination with carbon castor (without seat cushion)

Front seat height in mm (FSH)

Code	Castor	400	410	420	430	440	450	460	470	480	490	500	510
2495	Ø 100 x 30 mm, Black												
2496	Ø 125 x 30 mm, Black												

 Tyres: solid rubber, black

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

Seat height front in combination with aluminium castor (without seat cushion)

Front seat height in mm (FSH)

Code	Castor	Front seat height in mm (FSH)												
		400	410	420	430	440	450	460	470	480	490	500	510	
2483	Ø 100 x 37 mm, Silver													
2484	Ø 100 x 37 mm, Black													
2485	Ø 100 x 37 mm, White													
2486	Ø 100 x 37 mm, Red													
2487	Ø 100 x 37 mm, Blue													
2488	Ø 100 x 37 mm, Orange													
2489	Ø 125 x 37 mm, Silver													
2490	Ø 125 x 37 mm, Black													
2491	Ø 125 x 37 mm, White													
2492	Ø 125 x 37 mm, Red													
2493	Ø 125 x 37 mm, Blue													
2494	Ø 125 x 37 mm, Orange													

 Tyres: solid rubber, black

Steering wheel option

CODE	DESCRIPTION
903	Reinforced caster forks
2144	Reinforced steering head connection  recommended when using additional drives

Please select by ticking the relevant boxes

S Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

04 Rear wheels i.c. with seat height (tires CAT 07 and hand rims CAT 06)

The maximum permissible seat height difference between the front and rear seat height is 90 mm

RSH (mm) 370 380 390 400 410 420 430 440 450 460 470 480 490 500 510 520 530

- A
- B
- D
- E

CODE	RSH	DESCRIPTION	Ø
651	<input checked="" type="radio"/> B	Standard wheel, incl. quick release axle (pair)	22"
706	<input checked="" type="radio"/> B	Drum braked wheel with radial spokes and drum brake for accompanying person ⚠ Only in conjunction with 0° wheel camber CODE 423 Only in conjunction with push handles CODE 412 or 502 Wheel covering CODE 98 is recommended.	22"
651	<input checked="" type="radio"/> A	Standard wheel, incl. quick release axle (pair)	24"
2651	<input checked="" type="radio"/> A	Standard wheel black, incl. quick release axle (pair)	24"
706	<input checked="" type="radio"/> A	Drum braked wheel with radial spokes and drum brake for accompanying person ⚠ Only in conjunction with push handles CODE 412 or 502 Wheel overlap CODE 98 is recommended.	24"
848	<input checked="" type="radio"/> A	SILVERDESIGN with radial spokes and high flange rim incl. quick-release axle (pair)	24"
695	<input checked="" type="radio"/> A	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black ⚠ *Nicht i.V. mit PU-Bereifung CODE 902 Empfohlen ab 100 kg Nutzergewicht oder bei dynamischer Fahrweise nicht i.V.m. Carbolife Greifreifen CODE 849, 850, 853 nicht i.V.m. mit PU-Bereifung CODE 474	24"
695	<input checked="" type="radio"/> D	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black ⚠ Not i.c. with PU tires CODE 902 Recommended from 100 kg user weight or for dynamic driving Not i.c. with. Carbolife push rims CODE 849, 850, 853	25"
695	<input checked="" type="radio"/> E	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black ⚠ Not i.c. with PU tires CODE 902 Recommended from 100 kg user weight or for dynamic driving Not i.c. with. Carbolife push rims CODE 849, 850, 853	26"
2469	<input checked="" type="radio"/> A	Spinergy CLX, carbon rear wheel, spokes and hub black ⚠ *nicht i.V.m. PU-Bereifung CODE 474 und 902	24"
2470	<input checked="" type="radio"/> A	Spinergy LX, aluminum rear wheel, spokes, rim and hub black ⚠ *nicht i.V.m. PU-Bereifung CODE 474 und 902	24"
2471	<input checked="" type="radio"/> A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes white ⚠ *nicht i.V.m. PU-Bereifung CODE 474 und 902	24"
2472	<input checked="" type="radio"/> A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes orange ⚠ *nicht i.V.m. PU-Bereifung CODE 474 und 902	24"

Please select by ticking the relevant boxes

S Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

Rear wheel i.c. with seat height (incl. tyre and handrim)

The max permissible seat height difference between front and rear seat height is 100 mm!

RSH (mm) 370 380 390 400 410 420 430 440 450 460 470 480 490 500 510 520

- A
- B
- C
- D

CODE	RSH	DESCRIPTION	Ø
752	<input checked="" type="radio"/> B	Lightwheel incl. RightRun Light tyres and aluminum handrim black	22"
2465	<input checked="" type="radio"/> A	Six-Star incl. 8 bar high pressure tyres and aluminium handrim	24x1"
752	<input checked="" type="radio"/> A	Lightwheel incl. RightRun Light tyres and aluminum handrim black	24"
2466	<input checked="" type="radio"/> C	Cross-Rad incl. coarse studded tyres and stainless steel handrims (pair)	24x1.75"
2461	<input checked="" type="radio"/> A	Day-Lite aluminium drive wheel, black rim, hub and spokes, black aluminium handrim and black MBL Gazelle tyres. max. user weight 100kg	24x1"
2468	<input checked="" type="radio"/> D	Day-Lite aluminum rear wheel, black rim, hub and spokes, black aluminum handrim and black MBL Speedlite tyres. max. user weight 100kg	25x1"
2473	<input checked="" type="radio"/> A	Blacklight aluminum rear wheel, incl. Schwalbe Marathon Plus tyres and aluminum push rims, rim, hub and spokes black	24x1"

Complete wheels - please do not select handrims and tyres!

05 Horizontal rear wheel position (center of gravity)

	ACTIVE (Pos. - mm)			MEDIUM (Pos. - mm)		PASSIV (Pos. - mm)	
	1 - 100**	2 - 90**	3 - 80	4 - 70	5 - 60	6 - 50	7 - 40

Position

Measurement: Centre of back tube to centre of axle in mm
Drive wheel position 1 and 2 cannot be fitted in conjunction with frame short CODE 351

Please select by ticking the relevant boxes

S Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

Rear wheel options

CODE	DESCRIPTION
697	Release for tetra plegics, makes it easier to take off the drive wheel ⚠ Only i.c. with CODE 848 or CODE 695 drive wheel
423	0° wheel camber (track adjustable, wheel camber can be altered subsequently)
447	3° wheel camber (track adjustable, wheel camber can be altered subsequent-ly) in combination with drum brake CODE 706 restricted seat height variation

06 Handrims and handrim options

CODE	DESCRIPTION
445	Titanium, with 6 brackets ⚠ Only i.c. with active wheel CODE 695 and Spinergy wheel CODE 2469, 2470, 2471, 2472
493	Stainless steel, polished
494	Aluminum silver anodised ⚠ Not in combination with active wheel CODE 695
168	Optigripp-special handrim for tetraplegics
849	Curve L, aluminum black anodised, ergonomic handrim profile, H 31 mm
850	Curve L Tetra Grip, anti-slip coated, aluminum, suitable for quadriplegics, ergonomic handrim profile, H 31 mm
853	Gekko, aluminum black anodized with replaceable rubber lip, ergonomic hand rim profile, H 31mm
871	Double handrim for seat widths up to 480 mm ⚠ Only in conjunction with PU tyres CODE 902 Not in conjunction with drum brakes CODE 706 not suitable for very active use

Hand rim options

CODE	DESCRIPTION	Ø	Ø
166	Silicon hand rim cover, smooth, black ⚠ Not i.c. with Aluminum handrim CODE 494	22"	24"
692	Handrim distance narrow		
693	Handrim distance far		

Please select by ticking the relevant boxes

S Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

07 Tyres

CODE	DESCRIPTION	Ø
474	PU-tyres, puncture safe black	24x1"
486	Pneumatic tires 4 bar	22x1 3/8" - 24x1 3/8"
496	Pneumatic tires 8 bar	22x1" - 24x1"
902	PU-tyres, puncture safe ⚠ Not in combination with active wheel CODE 695	22x1" - 24x1"
902	PU-tyres, puncture safe ⚠ Not in combination with active wheel CODE 695	22x1 3/8" - 24x1 3/8"
897	Marathon-Plus-Evolution tyres, puncture protected	22x1" - 24x1"
363	Schwalbe ONE tires, no profile, puncture resistant	22x1" - 24x1"
395	Maxxis VN Master Alpha Protect tyre black, puncture resistant, 10 bar	22x1" - 24x1" - 25x1" - 26x1"

⚠ Tyres consist of a rubber compound which may leave permanent marks or be hard to remove from some surfaces (e.g. plastic, wooden or parquet flooring, rugs and carpets).
 ☒ We cannot accept liability for any abrasion damage to flooring.

08 Brakes




CODE	DESCRIPTION
305	Pressure brake for user
60/650	One-hand pressure brake left (incl. Brake lever long, hinged)
74/650	One-hand pressure brake right (including brake lever long, hinged)
681	Brake lever extension, foldable, firmly mounted
986	Attachable brake lever extension

09 Backrest height (BH)

DESCRIPTION	Backrest height in mm					
	(C-620)	(C-626)	(C-631)	(C-632)	(C-633)	(C-637)
Back strap, adaptable via Velcro straps adjustable +25 mm	250	300	350	400	450	500

Please select by ticking the relevant boxes Special construction/individual solution o.r. - on request Standard version: If no other selection is made, the standard version will be delivered.

Backrest variants

CODE	DESCRIPTION
2002	Back cover 20 mm wider  only in conjunction with CODE 235 or 292
2003	Back cover 40 mm wider  only in conjunction with CODE 235 or 292
593	Without back cover  recommended when using RIDE back systems

Back strap colours (seat strap always in black)

CODE	DESCRIPTION
235	Textil black
292	Mash, breathable , black
296	Net fabric, breathable , red

Please select by ticking the relevant boxes

S Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

10 Backrest

CODE	DESCRIPTION
410	Back with push handle, short
412	Back with push handle, long
141	Push handles, swivel-away ! only i.c. with Back without lumbar curve CODE 621
502	Backrest with push handle mounted to the frame tube, continuously height adjustable to 150 mm ! Not in combination with push handle code 140/141
140	Push handle integrated in the back tube, height adjustable up to 100 mm ! *Nicht i.V.m. Lumbalknick Code 622 nicht i.V.m. Rückenhöhe 250mm CODE 620
238	Folding push bar ! Not i.c. with push handles CODE 502

Backrest options

CODE	DESCRIPTION
29	Backrest, angle-adjustable from seat surface, +/-15° in 5° increments, can be adjusted subsequently ! from BH 300 mm only i.c. with push handle CODE 410 / 412 Not i.c. with Lumbar bend Code 62 Not i.c. with BH 250 mm not i.c. with side panel bracket CODE 24
621	Backrest without lumbar support
622	Backrest with lumbar support ! possible from BH 300 mm
2032	ErgoSeat Pro laterals, small, pair ! Recommended at back height 300 - 400 mm
814	Horizontal push bar, stabilises the back support under heavy strain ! not in combination with push handles CODE 141. Recommended from SB 460
913	Head support, 300 mm continuously height adjustable ! only in combination with push bar CODE 814

11 Ride System Back

Please specify the CODE from the RIDE order sheet:

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

12 Seat cushions





CODE	DESCRIPTION
560	Seat cushion 30 mm
561	Seat cushion 60 mm
7199	Netti Contour Breathable 3D cover
562	Velcro strip on seat belt

13 Ride System Seat


Please specify the CODE from the RIDE order sheet:

14 Arm supports and arm pads

1 = fixed screwed 2 = swivel up 3 = detachable 4 = lockable 5 = height-adjustable armrest 6 = with wheel cover

CODE	DESCRIPTION	FUNCTIONS
100	Aluminum arm support in frame colour with carbon insert	1,6
98	Side part made of aluminum in frame color with carbon insert and 50 mm wheel cover	1,6
81	Side guard, armrest short, height adjustable with one hand operation  from HSH 450 mm	2,3,4,5
84	Side guard, armrest long, height adjustable with one hand operation  from rear seat height 440 mm	2,3,4,5
748	Aluminium arm support in frame colour with carbon insert, incl. height adjustable arm support  Not in combination with light brake Code 595 from rear seat height 440 mm	1,5,6
783	Carbon fiber side guard	1,6
302	Aluminium Light arm support in frame colour  from the rear seat height 430 mm	1

Side panel option

CODE	DESCRIPTION
24	Swing-away side panel bracket  only i.c. with CODE 98, 100, 783 or without side panel not i.c. with back angle adjustable CODE 29

Please select by ticking the relevant boxes

S Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

15 Leg supports

CODE	DESCRIPTION	
93	Removable, swing away	Pair
759	Removable, swing away	Left
760	Removable, swing away	Right
92	Can be removed, moved away and swung up	Pair
52	Amputee leg support	Pair
4508	Amputee leg support	Left
4507	Amputee leg support	Right
293	Compact 78°	Pair
3532	Shortened, can be removed, moved away and swung up A only i.C. with leg rest compact CODE 293	Pair 270-360 mm
94	without leg rests	

A CODE 92 only i.C. with footrest CODE 798 and not i.C. with frame short CODE 351

Footrests

LLL (mm) 390 400 410 420 430 440 450 460 470 480 490

B
C

CODE	LSL	DESCRIPTION	depth
312	B	*Fußstütze durchgehend aus stabilem Aluminiumprofil in schwarz hochklappbar, höhen- und winkelverstellbar	
315	B	Footrest continuous aluminum in black fold up, height and angle adjustable	
798	C	*Kunststoff Fußstützen geteilt, hochklappbar und höhen-/winkelverstellbar A from seat width 380 mm only i.C. with CODE 92 Legrests can be removed, swivelled away and upwards	160 mm
808	C	*Aluminiumfußstützen in schwarz geteilt, hochklappbar, tiefenverstellbar, höhen- und winkelverstellbar	150 mm
4312	B	LED footrest made of sturdy aluminum in black continuous, height/depth and angle adjustable, incl. Bluetooth module A From seat width 360 mm	100 mm
4313	B	LED footrest made of sturdy aluminum in black continuous, height / depth and angle adjustable A From seat width 360 mm	100 mm

Please select by ticking the relevant boxes Special construction/individual solution o.r. - on request Standard version: If no other selection is made, the standard version will be delivered.

Footrests options

CODE	DESCRIPTION
925	Operating aid for locking device, in case of limited hand function A only in combination with upper leg support compact CODE 293
359	Calf belt

16 Frame colours

CODE	DESCRIPTION
130	Titanium grey
206	Matt black
224	Blue-Metallic
227	Red Metallic
4044	Red Metallic Matt
4049	Olive green Matt
4050	Sky Blue
4051	Chalk
4922	Metallic green
4919	Silverline

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

17 Options

hand and spoke protection

CODE	DESCRIPTION
489	Transparent ⚠ Not i.c. with Spinergy Wheel CODE 2469, 2470, 2471, 2472

Support castors

CODE	DESCRIPTION
691	Anti-Tip, 1 pair, swivelling (recommended) ⚠ Not i.c. with step tube CODE 309
712	1 anti-tip, swivelling, mounted left ⚠ Not in combination with pedal tube CODE 309/4930, not in combination with shunting castors CODE 746
713	1 anti-tip, swivelling, mounted right ⚠ Not in combination with pedal tube CODE 309/4931, not in combination with shunting castors CODE 746

Other accessories

CODE	DESCRIPTION
746	1 pair shunting castors, e.g. for tight spaces or in an aeroplane ⚠ Not i.c.w. pedal tube CODE 309 or support castors CODE 691, from RSH 420 mm
833	Safety belt
970	Crutch holder ⚠ only i.V. with tread pipe CODE 309/4930/4931 or CODE 691/712/713
819	Reflectors ⚠ not in v.v.m. CODE 752, 2473, 2461 and 2468
309	Step tubes (1 pair)
4930	1 step tube, mounted on the left ⚠ not in combination with anti-tip-wheels, CODE 691/712 and anti-tip-wheels, CODE 746
4931	1 step tube, mounted on the right ⚠ not in combination with anti-tip-wheels, CODE 691/713 and anti-tip-wheels, CODE 746
	205542100 Hand compressor
679	Folding lock

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

Therapy tables

CODE	DESCRIPTION
929	Therapy table plastic, transparent, adjustable from 380 - 480 mm seat width ⚠ only in combination with side panel CODE 84
930	Therapeutic table for manual wheelchairs made of plastic, transparent, for sliding on, for defined seat width ⚠ only in combination with side panel CODE 84

⚠ With 24" wheels and a rear seat height of less than 470 mm, there is a resulting limitation in terms of armrest height with use of the therapy table Code 929/930

Xtrends options

Item	DESCRIPTION	HMV
261519300	X-TREME Backpack	
261519600	Wheel pouch „BLACK WHEEL CASE“ fitting for max. 2 x 24" wheels resp. each 1 x 25" or 26" wheel	18.99.99.0999
1074231	Wheel pouch „MEYRA ACTIVE“, fitting for max. 3 x 28" wheels	
206964600	3M Spoke reflectors	18.99.99.0999

USER DATA

First name

Name

Street

ZIP CODE

City

Country

Birthday

Diagnosis 1

Diagnosis 2

Tel.

Mobil

E-mail

Order number

Health insurance fund / cost unit

Specialist trade Contact person/phone.

Supply specialist MEYRA

Approval info from week

ANATOMICAL DATA (IN MM)

1) Seat depth

2) Seat width

3) Chest width

4) Chest depth

5) Elbow height

6) Armpit height

7) Back height


8) Head height

9) Forearm length

10) LLL

Body height

Weight (kg)



Remarks

I accept the Terms and Conditions of Meyra Distribution GmbH (valid as of January 2023)

<https://www.meyra.com/gtc/>

Date

City

Signature



10 Code 29



15 Code 52



08 Code 73



14 Code 81




14 Code 84



15 Code 92



15 Code 93



14 Code 98



14 Code 100



10 Code 140




10 Code 141



10 Code 238



15 Code 293



14 Code 302



08 Code 305



15 Code 315




10 Code 410



10 Code 814



15 Code 4312




05 Code 423




05 Code 447



10 Code 621



10 Code 622



08 Code 650




08 Code 681



05 Code 697



14 Code 748



14 Code 783



15 Code 798



15 Code 808