


# EUROCHAIR2 HD

2.850

 **Allowed user weight**  
300 kg





Extremely sturdy



One-piece footboard



Increased stability through the use of a double shear



Reinforced seat belt

## *maximum stability*

---

### **EFFICIENCY**

- Can be used as a reinforced wheelchair for permanent everyday use individually for heavy users up to 300 kg
- The targeted implementation of fixed frame connection elements provide the folding wheelchair with the stability required for its field of application.
- Extensive network of specialist retailers and suppliers ensures a secure supply of spare parts over the longer term

### **THERAPEUTIC BENEFIT**

- Independent locomotion of a heavyweight person up to 300 kg user weight, e.g. obesity and/or care and transport in barrier-free indoor and outdoor areas
- Independent mobility is supported as far as possible by good adaptation of the seat, backrest and chassis to the user
- The transverse push bar and the continuous footplate provide the user with the greatest possible support in the sitting position

### **FIELD OF USE**

- Suitable for heavy people up to 300 kg
- The supply and transfer for user and accompanying person is facilitated
- Use in old people's and nursing homes, therapy and rehabilitation centers or in the home to support therapeutic goals.

ORDER

COST ESTIMATE

CUSTOM DESIGN

Please send the order form by e-mail to:

[info@meyragroup.com](mailto:info@meyragroup.com)

Customer service: +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

**MEYRA**



### Standard configuration

- Reinforced back strap
- Reinforced seat belt
- One-piece footboard

- Drum Brake
- Transverse push bar



### Allowed user weight

300 kg



### Hints

All prices are subject to the statutory value added tax!

Our Terms and Conditions as stated at [www.meyra.de/AGB](http://www.meyra.de/AGB) shall apply

You can find information on the measurement process at [www.meyra.de/messverfahren](http://www.meyra.de/messverfahren)

When transported in public transport (e.g. train), the dimensions of the wheelchair may be higher than the guide values of the transport company. Please inquire in advance.

Valid from 01.01.2026 – 31.12.2026.

Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at [www.kisss-by-meyra.de](http://www.kisss-by-meyra.de)

You avoid queries and incorrect orders thanks to the buildability check

Standard test of the brake at 7° gradient, actuating forces on the brake lever 80 N

Please note the overall width for use in the domestic environment.

Passenger transport in a wheelchair as a seat in a motor vehicle is not permitted.

Auxiliary drives are only permitted if a combination declaration is available.

**Technical specifications**

Seat widths in mm	700 / 750 / 800
Width ready to drive in mm from	920 / 970 / 1020
Width folded in mm from	335
Seat depth in mm	460 / 500
Overall height in mm	960
Back support height in mm	430
Arm support height in mm	230 - 330
Length with footrest in mm	max. 1140
Length without footrests in mm	max. 900
User weight	300 kg
Empty weight from	35 kg
Permitted total weight in kg	335 kg
Transport weight	28 kg
Rear wheel	610 (24")
Brake test according to STANDARD	7°

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

## 01 Seat width (SW)

CODE	DESCRIPTION
3368	SW 700 mm (up to 300 kg user weight)
3370	SW 750 mm (up to 300 kg user weight)
3372	SW 800 mm (up to 300 kg user weight)

## 02 Seat depth (SD)

CODE	DESCRIPTION
619	SD 460 mm
792	SD 500 mm

## 03 Front seat height (VSH mm) in combination with castor and drive wheel (without seat cushion)

Please select your desired seat height by choosing a possible combination of seat height and wheel size.  
(Only 24 x 13/8" drive wheel).

Code	Ø Lightwheel	475	500
154	Ø 142 Soft solid rubber	<input type="checkbox"/>	<input type="checkbox"/>
157/900	Ø 200 Flexel	<input type="checkbox"/>	<input type="checkbox"/>

**⚠** Selecting the FSH automatically configures a standard steering wheel and the appropriate steering fork.  
The rear seat height is automatically determined by the standard seat angle of approx. 4 degrees, which corresponds to a difference of approx. 30 mm.

## Seat Cushions

CODE	DESCRIPTION
561	Seat cushion 60 mm
714	*Inkontinenzbezug für Sitzkissen, grau

Please select by ticking the relevant boxes

Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

## 04 Push Rims

CODE	DESCRIPTION
493	STAINLESS STEEL
692	handrim spacing narrow
693	handrim spacing far <b>!</b> Only i.c. with Code 493 stainless steel handrim

## 05 Tyres

CODE	DESCRIPTION
904	Flexel tyres, puncture-proof

## 06 Brakes

CODE	DESCRIPTION
680/706	Pressure brake for user and drum brake for accompanying person
986	Brake lever extension, slide-on, 1 pair

## 07 Back support belt height

CODE	DESCRIPTION	Height
442	Back in reinforced version	430 mm

## 08 Backrest

CODE	DESCRIPTION
622	Backrest with lumbar support

### Backrest options

CODE	DESCRIPTION
814	Horizontal push bar, stabilises the back support under heavy strain

Please select by ticking the relevant boxes

 S Special construction/individual solution o.r. - on request

 Standard version: If no other selection is made, the standard version will be delivered.

### 09 Arm Supports and Arm Pads

CODE	DESCRIPTION
106	Height-adjustable side section, depth-adjustable armrest cushions

### 10 Leg supports

CODE	DESCRIPTION
94	Without leg supports and footrest
93	Leg supports, removable and swivelling

### 11 Footrests

CODE	LLL (mm)	DESCRIPTION	depth
	LLL (mm) 350 360 370 380 390 400 410 420 430 440 450 460 470 480 490		
	<b>A</b>		
54	<b>A</b>	Continuous footrest, 60 mm depth adjustable (in 4 steps), flip-up, height and angle adjustable	150 mm

### 12 Leg support and footrest options

CODE	DESCRIPTION
822	Shoe fastening strap (pair)

### 13 Frame Colours

CODE	DESCRIPTION
4919	Silverline

### 14 Seat-/back strap colours

CODE	DESCRIPTION
287	Deep black, polyester

Please select by ticking the relevant boxes Special construction/individual solution o.r. - on request Standard version: If no other selection is made, the standard version will be delivered.

## 15 Options around the wheelchair

### Hand and spoke protectors

CODE	DESCRIPTION
489	Transparent

### Support castors

CODE	DESCRIPTION
691	Support rollers, removable (1 pair)

### Other options

CODE	DESCRIPTION
585	Infusion post "UNIVERSAL"
819	Reflectors
833	Safety belt