


EUROCHAIR2 HD

2.850

 **Allowed user weight**
300 kg





Extremely sturdy



One-piece footboard



Increased stability through the use of a double shear



Reinforced seat belt

maximum stability

EFFICIENCY

- Can be used as a reinforced wheelchair for permanent everyday use individually for heavy users up to 300 kg
- The targeted implementation of fixed frame connection elements provide the folding wheelchair with the stability required for its field of application.
- Extensive network of specialist retailers and suppliers ensures a secure supply of spare parts over the longer term

THERAPEUTIC BENEFIT

- Independent locomotion of a heavyweight person up to 300 kg user weight, e.g. obesity and/or care and transport in barrier-free indoor and outdoor areas
- Independent mobility is supported as far as possible by good adaptation of the seat, backrest and chassis to the user
- The transverse push bar and the continuous footplate provide the user with the greatest possible support in the sitting position

FIELD OF USE

- Suitable for heavy people up to 300 kg
- The supply and transfer for user and accompanying person is facilitated
- Use in old people's and nursing homes, therapy and rehabilitation centers or in the home to support therapeutic goals.

ORDER

COST ESTIMATE

CUSTOM DESIGN

Please send the order form by e-mail to:

info@meyragroup.com

Customer service: +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Basic equipment

- Reinforced back strap
- Reinforced seat belt
- One-piece footboard

- Drum Brake
- transverse push bar



Allowed user weight

300 kg



Hints

All prices are subject to the statutory value added tax!

Our Terms and Conditions as stated at www.meyra.de/AGB shall apply

You can find information on the measurement process at www.meyra.de/messverfahren

When transported in public transport (e.g. train), the dimensions of the wheelchair may be higher than the guide values of the transport company. Please inquire in advance.

Valid from 01.01.2025 – 31.12.2025.

Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de

You avoid queries and incorrect orders thanks to the buildability check

Standard test of the brake at 7° gradient, actuating forces on the brake lever 80 N

Please note the overall width for use in the domestic environment.

Passenger transport in a wheelchair as a seat in a motor vehicle is not permitted.

Auxiliary drives are only permitted if a combination declaration is available.



Technical specifications

Seat widths in mm	700 / 750 / 800
Width ready to drive in mm from	920 / 970 / 1020
Width folded in mm from	335
Seat depth in mm	460 / 500
Overall height in mm	960
Back support height in mm	430
Arm support height in mm	230 - 330
Length with footrest in mm	max. 1140
Length without footrests in mm	max. 900
User weight	300 kg
Empty weight from	35 kg
*Zul. Gesamtgewicht in kg	335 kg
Transport weight	28 kg
Rear wheel	610 (24")
Brake test according to STANDARD	7°

☐ Please select by ticking the relevant boxes

S

 Special construction/individual solution o.r. - on request

☐ Standard version: If no other selection is made, the standard version will be delivered.

01 Seat width (SW)

CODE	DESCRIPTION
3368	SW 700 mm (up to 300 kg user weight)
3370	SW 750 mm (up to 300 kg user weight)
3372	SW 800 mm (up to 300 kg user weight)


02 Seat depth (SD)

CODE	DESCRIPTION
619	SD 460 mm
792	SD 500 mm

03 Front seat height (VSH mm) in combination with castor and drive wheel (without seat cushion)

*Bitte wählen Sie Ihre gewünschte Sitzhöhe durch Auswahl einer möglichen Kombination aus Sitzhöhe und Radgröße.
(Nur 24 x 13/8" Antriebsrad).

Code	Ø Lightwheel	475	500
154	Ø 142 Soft solid rubber		
157/900	Ø 200 Flexel		

 *Durch Wahl der VSH wird automatisch ein Standardlenklauftrad sowie die passende Lenkgabel konfiguriert.
Die hintere Sitzhöhe ergibt sich automatisch durch die Standard-Sitzneigung von ca. 4 Grad, das entspricht ca. 30 mm Differenz.

Seat cushions

CODE	DESCRIPTION
561	Seat cushion 60 mm
714	*Inkontinenzbezug für Sitzkissen, grau

☐ Please select by ticking the relevant boxes☒ S Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**04 Handrims**

CODE	DESCRIPTION
493	STAINLESS STEEL
692	handrim spacing narrow
693	handrim spacing far
⚠ Only i.c. with Code 493 stainless steel handrim	

05 Tyres

CODE	DESCRIPTION
904	Flexel tyres, puncture-proof

06 Brakes

CODE	DESCRIPTION
680/706	Pressure brake for user and drum brake for accompanying person
986	Brake lever extension, slide-on, 1 pair

07 Back support belt height

CODE	DESCRIPTION	Height
442	Back in reinforced version	430 mm

08 Backrest

CODE	DESCRIPTION
622	Backrest with lumbar support

Backrest options

CODE	DESCRIPTION
814	Horizontal push bar, stabilises the back support under heavy strain

☐ Please select by ticking the relevant boxes☒ S Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**09 Arm supports and arm pads**

CODE	DESCRIPTION
106	Height-adjustable side section, depth-adjustable armrest cushions

10 Leg supports

CODE	DESCRIPTION
94	Without leg supports and footrest
93	Leg supports, removable and swivelling

11 Footrests

LLL (mm)																350	360	370	380	390	400	410	420	430	440	450	460	470	480	490
A																														
CODE	LLL (mm)		DESCRIPTION												depth															
54	A		Continuous footrest, 60 mm depth adjustable (in 4 steps), flip-up, height and angle adjustable												150 mm															

12 Leg support and footrest options

CODE	DESCRIPTION
822	Shoe fastening strap (pair)

13 Frame colours

CODE	DESCRIPTION
4919	Silverline

14 Seat-/back strap colours

CODE	DESCRIPTION
287	Deep black, polyester

☐ Please select by ticking the relevant boxes

S

 Special construction/individual solution o.r. - on request

☐ Standard version: If no other selection is made, the standard version will be delivered.

15

Options around the wheelchair

Hand and spoke protectors

CODE	DESCRIPTION
489	Transparent

Support castors

CODE	DESCRIPTION
691	Support rollers, removable (1 pair)

Other options

CODE	DESCRIPTION
585	Infusion post "UNIVERSAL"
819	Reflectors
833	safety belt